

What Is Claimed Is:

Sub  
A

1. A decoding method for demodulating a received signal available in serial code concatenation in a code-division multiple access transmission system, a two-step coding being carried out at the transmitting end of the transmission system, a first step of the two-step coding including a Hadamard orthogonal multi-step inner code, a second step of the two-step coding including an outer error-correcting code of a predefined rate, the method comprising:

providing a soft-in/soft-out decoder in a receiver of the transmission system, a first decoder step of the soft-in/soft-out decoder including an inner decoder, a second decoder step of the soft-in/soft-out decoder including an outer decoder; and

processing soft values as reliability information at an output and an input of the soft-in/soft-out decoder, a soft output of the inner decoder being a soft input for the outer decoder, a channel reliability information output from a preceding demodulation being an input for the inner decoder.

2. The method as recited in claim 1 wherein the inner code includes a 32-step modulation.

3. The method as recited in claim 1 wherein the inner code includes a 64-step modulation.

4. The method as recited in claim 1 wherein the outer code includes a convolution code.

5. The method as recited in claim 1 wherein the outer code includes a block code.

6. The method as recited in claim 1 wherein the reliability information includes L-values.

7. The method as recited in claim 1 wherein a soft input of the inner decoder includes a-priori information for systematic bits of Walsh functions of the inner code, the a-

206070" OF 4007

priori information being useable by the inner decoder for decoding the inner code.

8. The method as recited in claim 7 wherein the inner decoder includes a maximum a-posteriori decoder.

5

9. The method as recited in claim 1 wherein to enhance reliability of decisions of the inner decoder, a soft output of the outer decoder is fed back as a soft input to the inner decoder as a-priori information for systematic bits of Walsh functions of the inner code.

10

Sub 7 The method as recited in claim 7 wherein the inner decoder includes a maximum a-posteriori decoder and wherein the a-priori information is made available to the inner decoder as reliability values in an a-priori vector  $L(u)$  so that the inner decoder provides L-values for estimated symbols of an inner decoder soft value output vector  $L(\hat{u})$ , an amount  $|L(\hat{u}_k)|$  of the L-values indicating a reliability of a respective decision and an operational sign of the  $L(\hat{u}_k)$  representing a hard decision.

15

11. The method as recited in claim 9 wherein the inner decoder includes a maximum a-posteriori decoder and wherein the a-priori information is made available to the inner decoder as reliability values in an a-priori vector  $L(u)$  so that the inner decoder provides L-values for estimated symbols of an inner decoder soft value output vector  $L(\hat{u})$ , an amount  $|L(\hat{u}_k)|$  of the L-values indicating a reliability of a respective decision and an operational sign of the  $L(\hat{u}_k)$  representing a hard decision.

20

12. The method as recited in claim 1 wherein the receiver includes a coherent receiver structure, wherein a soft input of the inner decoder includes a-priori information for systematic bits of Walsh functions of the inner code and wherein the inner decoder includes a maximum a-posteriori decoder, the maximum a-posteriori decoder calculating, starting from an input vector  $L_C \cdot y$  having a specific reliability  $L_C$  and from an a-priori information vector  $L(u)$ , as a decoder result, a weighted decision including reliability L-values for estimated symbols, the L-values including an extrinsic term  $L_e(\hat{u}_k)$ .

25

30

13. The method as recited in claim 1 wherein the receiver includes a coherent receiver structure, wherein a soft input of the inner decoder includes a-priori information for systematic bits of Walsh functions of the inner code, and wherein the inner code includes a Hadamard code, the Hadamard code being decoded by:

5 adding an a-priori information vector  $L(u)$  for systematic bits of a Walsh function of the Hadamard code to an input vector  $L_C y$  from a channel;

performing a fast Hadamard transformation so as to provide a fast Hadamard transform resultant vector  $w$ ;

10 then generating exponential functions with  $\frac{1}{2} \cdot w_j$  as an argument,  $w_j$  being a respective element of the vector  $w$ ; and

adding, dividing and expressing logarithmically elements of a result vector  $z$  for each symbol  $\hat{u}_k$  to be decoded according to the equation:

$$\ln \frac{\sum_{j, u_k = +1}^{N-1} z_j}{\sum_{j, u_k = -1}^{N-1} z_j} = \ln \frac{\sum_{j, u_k = +1}^{N-1} \exp(\frac{1}{2} w_j)}{\sum_{j, u_k = -1}^{N-1} \exp(\frac{1}{2} w_j)} = \ln \left( \sum_{j, u_k = +1}^{N-1} \exp(\frac{1}{2} w_j) \right) - \ln \left( \sum_{j, u_k = -1}^{N-1} \exp(\frac{1}{2} w_j) \right)$$

15  $z_j$  being a respective element of the resultant vector  $z$ ,  $j$  being a respective vector element index,  $N$  being a size of the Walsh functions of the inner code.

20 14. The method as recited in claim 1 wherein a result of the inner decoder for a bit  $\hat{u}_k$  includes a-priori information  $L(u_k)$  about a bit to be decoded, channel information  $L_C y_{\text{sys}(k)}$  about the bit to be decoded, and extrinsic information  $L_e(\hat{u}_k)$ , channel information and a-priori information on all other bits of a demodulator output vector  $y$  or of a transmitted Walsh function of the inner code being included in the extrinsic information  $L_e(\hat{u}_k)$ .

25 15. The method as recited in claim 1 wherein the receiver includes an incoherent receiver structure and wherein the inner decoder includes a maximum a-posteriori decoder, the maximum a-posteriori decoder calculating, starting from a square-law-  
30

combining fast Hadamard transform resultant decision vector  $w$  and from an a-priori vector  $L(u)$ , as a decoder result, a weighted decision including the  $L$ -values for estimated symbols, the  $L$ -values including an extrinsic term  $L_e(\hat{u}_k)$ .

5 16. The method as recited in claim 1 wherein the receiver includes an incoherent receiver and wherein the outer decoder includes a maximum a-posteriori decoder, the soft output of the inner decoder including a-priori information for systematic bits of Walsh functions of the inner code useable for decoding of the inner code.

10 ~~Sub~~ 17. A decoding device for demodulating a received signal available in serial code concatenation in a code-division multiple access transmission system, a two-step coding being carried out at the transmitting end of the transmission system, a first step of the two-step coding including a Hadamard orthogonal multi-step inner code, a second step of the two-step coding including an outer error-correcting code of a predefined rate, the device comprising:

15 a soft-in/soft-out decoder disposed in a receiver of the transmission system, a first decoder step of the soft-in/soft-out decoder including an inner decoder, a second decoder step of the soft-in/soft-out decoder including an outer decoder, soft values being processed as reliability information at an output and an input of the soft-in/soft-out decoder, a soft output of the inner decoder being a soft input for the outer decoder, a channel reliability information output from a preceding demodulation being an input for the inner decoder.

20 18. The device as recited in claim 17 wherein the inner code includes a 32-step modulation.

25 19. The device as recited in claim 17 wherein the inner code includes a 64-step modulation.

30 20. The device as recited in claim 17 wherein the outer code includes a convolution code.

21. The device as recited in claim 17 wherein the outer code includes a block code.

22. The device as recited in claim 17 wherein the reliability information includes L-values.

5

23. The device as recited in claim 17 wherein to enhance reliability of decisions of the inner decoder, a soft output of the outer decoder is fed back as a soft input to the inner decoder as a-priori information for systematic bits of Walsh functions of the inner code.

10

24. The device as recited in claim 17 further comprising a RAKE receiver disposed upstream from the inner decoder, an output of the RAKE receiver including the channel reliability information output from the preceding demodulation.

10043710.010902